



TECHNICAL DATA

2500 USG	Model	5000 USG
40m3/F	Cyclic Capacity	90 m3/F
3 BAR	Max Water P.S.I.	3 BAR
68 cm	Lenght	100 cm
47 cm	Diameter	47 cm
8 Kg	Weight	17 Kg






HOW TO USE:

The length of service between recharges will vary depending on water hardness and water pressure. Please, note: the water produced by YC water softener is not drinkable!

Procedure:

Connect a long hose to the water source and the water filter (A) Insert the carbon cartridge (A) into place - Connect the unit (A) to the YC water softener (B) Attach the other end of YC Water softener (B) with the consume's hose. Turn the water on and let it flow for a few minutes. YC water softener is now ready to use








HOW TO REGENERATE:

The YC water softener system must be regenerated with rock salt. This process can be done in approximately twenty minutes.

Procedure:

Unscrew and remove water filter (A) Fill the cartridge with the necessary quantity of salt and screw it back Open the input valve and let the water flows slowly about 5 or 10 minutes Turn water off and wait few minutes Turn water back on for 1 minute and repeat this 3 or 4 times. Fully open the input valve to flush the unit and remove further residual salt brine YC water softener is now ready to deliver water without calcium







YC WATER SOFTENER IS EQUIPPED WITH THE FOLLOWING ACCESSORIES:



TWO FITTINGS YC-104

Suitable for 19mm (3/4") Ø. Plug-in fitting. Water pipe fitting.



COUNTER-LITER YC-103

Suitable for 13mm (1/2") Ø Plug-in fitting. Water pipe fitting.



FILTER HOUSING YC-105

Suitable for 13 mm (1/2") and 15 mm (5/8") hose.



CARBON CARTRIDGE YC-101

Suitable for 19mm (3/4") Ø. Plug-in fitting. Water pipe fitting.



SALT CARTRIDGE YC-102

Suitable for 13mm (1/2") Ø Plug-in fitting. Water pipe fitting.



HOSE YC-106

Suitable for 13 mm (1/2") and 15 mm (5/8") hose.



info@yachtclean.it www.yachtclean.it